

Die neue Speras E2R kann sowohl über USB-C geladen werden (5V / 2A) als auch andere Geräte laden !



**SPERAS E2R 1500LM**

Outdoor Tactical Infinity

### Various Settings( Outdoor, Tactical, Infinity)

To meet the desired requirements of outdoor use, tactical, law enforcement, security and defense, camping, hunting or personal EDC use etc.

**With OTG connector**  
Easy to charge various electronic products acting as a powerbank with a 2A current output.

**Supports TYPE C 5V/2A charging**  
Increasing charge rate by a 100%  
Charging time: 3.5h

Red LED while charging Green LED while full

**SPERAS E2R 1500LM**

**Accurate battery capacity indication while turn on flashlight**

- >70% Green
- 30%-70% Orange
- <30% Red
- <10% Red Flash





**Standar Accessories**

- 1\* Dual direction pocket clip
- 1\* Type-C Cable
- 1\* OTG
- 1\* Holder
- 1\* lanyard
- 2\* O-rings
- 1\* manual

**Operational accessories**

- 1\* 21700 battery (5000)
- 1\* Tube Insert (TWS)

**SPERAS E2R 1500LM**

FL 1 STANDARD		High	Medium	Low	ECO	Strobe	SOS
	Output (Setting 1)	1500LM (900LM)	400LM	60LM	10LM	1500LM	60LM
	Output (Setting 2)	1500LM (900LM)	400LM	—	10LM	1500LM	60LM
	Runtime	2.6h	6.25h	50h	500h	—	—
	Beam Intensity	17,824cd	6,052cd	732cd	136cd	—	—
	Beam Distance	267m	156m	54m	23m	—	—
	LED	LUMINUS LED					
	Impact Distance	1.5m					
	Waterproof	IP68 (2 meter submersible)					
	Charging Time	3.5h					
	Output (Setting 3)	1500LM~~20LM(The running time depends on usage situation)					



### Speras E2R

- 1500 lm, 267m beam distance;
  - Very compact handheld and with very nice structure and heat dissipation
  - Programme settings with outdoor, tactical, infinity functions.  
Easy to choose the settings and each setting has very simple humanized operation UI; especially the innovative tactical operation UI;
    - For the setting 1(Outdoor), we specially the 60lm mode for walking and 10 lm beam shot at night.
    - For the setting 2(Tactical), you can easy to access the one-touch strobe, one-touch turbo, ECO mode or change mode.
    - For the setting 3(Infinity),you can gradual increase/decrease of lumen output to obtain desired lighting of object/target
  - Easy to activate the memory mode function or close it.
  - Support 5V 2A Type C charging, increasing charge rate 100%
  - Support Type C 2A discharging with the OTG connector, to fast charge various electronic products as a powerbank.
  - Firm dual direction stainless steel pocket clip for multiple carry Options.
  - Intelligent temperature control system(ITS); Accurate battery capacity detection; over discharge protection and reverse polarity protection
  - Application: EDC, camping, tactical, defence, law enforcement, hunting, outdoor personal use, etc
- Length:120.5mm/4.82in
  - Head diameters: 28.5mm/1.12in
  - Body diameters:27mm/1.06in
  - Net Weight: 0g/3.53oz
  - Light Source: High performance Luminus LED
  - Powered by: 1\*21700 OR 2\*CR123A batteries
  - Material: AL6061 Aluminum Alloy

**Price: 64,50 Euro**

Im Preis enthalten: 1 x 21700 Batterie mit 5000 mAh.

Details: [www.new-tech-products.com/support/SPERAS\\_E2R\\_EN.pdf](http://www.new-tech-products.com/support/SPERAS_E2R_EN.pdf)

Please send your orders to: [auftragsbearbeitung@ntp-gmbh.com](mailto:auftragsbearbeitung@ntp-gmbh.com)

All prices are plus statutory VAT

Interested in more?

Here you can see an overview of the NTP-Assortments:

[www.new-tech-products.com/products/pdf/NTP-Products-Overview.pdf](http://www.new-tech-products.com/products/pdf/NTP-Products-Overview.pdf)



Best Regards

Rolf Olejniczak-Burkert  
New-Tech-Products Handels GmbH

Phone : +49 (0) 7308 / 811 00 - 0 (Zentrale)

Fax : +49 (0) 7308 / 811 00 - 19

[www.new-tech-products.com](http://www.new-tech-products.com)

Nersinger Straße 14-16 • 89275 Elchingen • Germany  
Sitz Ulm - HRB 4496 Amtsgericht Ulm

Geschäftsführer: Rolf Olejniczak-Burkert  
UST-IDNr.: DE813398643

Should you (%Email%) no longer need this Email-Newsletter,  
just reply with [REMOVE](#) in the subject line.